

RWELD

Inverter Technology



Always ahead for it's Quality, Workability & Availability



CE AN ISO 9001-2015
CERTIFIED COMPANY





Model	ARC 200 SG
Input Voltage (V)	220 V ± 15% (1 Phase)
Output Current (A)	20 - 200
Rated Input Power (KVA)	5.8
IGBT / MOSFET	IGBT
Welding Rod Size can be use	1.6 - 3.15
Weight (Kg.)	4.600
Dimension (mm)	490 x 210 x 370
Accessories	Welding Cable with Holder Earthing Cable with Clamp

Model	ARC 250 SG
Input Voltage (V)	220 V ± 15% (1 Phase)
Output Current (A)	20 - 250
Rated Input Power (KVA)	8.2
IGBT / MOSFET	IGBT
Welding Rod Size can be use	1.6 - 3.15
Weight (Kg.)	4.900
Dimension (mm)	490 x 210 x 370
Accessories	Welding Cable with Holder Earthing Cable with Clamp

Model	ARC 300 SG
Input Voltage (V)	220 V ± 15% (1 Phase)
Output Current (A)	20 - 300
Rated Input Power (KVA)	10.5
IGBT / MOSFET	IGBT
Welding Rod Size can be use	1.6 - 4.0
Weight (Kg.)	5.300
Dimension (mm)	490 x 210 x 370
Accessories	Welding Cable with Holder Earthing Cable with Clamp



Model	ARC 300 ZX
Input Voltage (V)	220-415 V ± 15% (1-2 Phase)
Output Current (A)	20 - 300
Rated Input Current (A)	21 (1-PH) & 12 (2-PH)
IGBT / MOSFET	IGBT
Welding Rod Size can be use	1.6 - 4.0
Weight (Kg.)	7.200
Dimension (mm)	490 x 210 x 370
Accessories	Welding Cable with Holder Earthing Cable with Clamp

Model	ARC 400 ZX
Input Voltage (V)	220-415 V ± 15% (1-2-3 Phase)
Output Current (A)	20 - 400
Rated Input Current (A)	25 (1-PH), 12.7 (2-PH) & 12.7 (3-PH)
IGBT / MOSFET	IGBT
Welding Rod Size can be use	1.6 - 5.0
Weight (Kg.)	8.800
Dimension (mm)	490 x 210 x 370
Accessories	Welding Cable with Holder Earthing Cable with Clamp

